

YM-BD PANELVISOR™

PanelVisors™ are made from Lexan with UV protective coating on both sides. The visor will protect your Yanmar control panel from weathering, both sun and water. It attaches directly to the panel so additional holes are not required. New hardware (4 machine screws, flat washers, and nuts) is included to replace your current fasteners.

INSTALLATION

- 1 Remove old fasteners from the four corners of your Yanmar B-digital type panel.
- 2 Place PanelVisor™ over the panel and insert screws. Attach washers and nuts to the back side of the mounting surface. Nuts should be run down to the surface, then gently tightened (1/8 turn) until snug. Do not over tighten because distortion or damage to both the Visor and panel may result.

CARE

A clean freshwater rinse and quick wipe with soft clean T-shirt material is all that is needed for cleaning the Lexan XL102UV. Your panel won't break, but if you scratch it, a gentle rubbing with a plastic polish will restore its clarity.

NOTE

The PanelVisor™ will do a good job of weatherproofing your panel. Sealant is optional. If you want to make it drip proof, apply a 1/8" bead of clear marine sealant in the small margin on the sides and top. Add the sealant around the outside of the panel BEFORE installing the PanelVisor™.



2904 29th Ave E
Bradenton, FL 34208
PanelVisor@SeaworthyGoods.com
www.SeaworthyGoods.com
941.448.9173